

IN THE CLAIMS

Re-write Claims 1, 11, 18, 21 and 22 as follows.

Cancel Claim 20.

1. (original) An integrated circuit chip comprising:  
a plurality of random access memory (RAM) blocks,  
wherein each of the RAM blocks is accessible by system  
circuitry located on the chip during normal operation  
of the chip;

a plurality of test modules, each being coupled to  
a corresponding one of the RAM blocks, wherein each of  
the test modules enables access to a corresponding one  
of the RAM blocks, independent of the system circuitry;  
and

a dedicated test bus coupled to each of the test  
modules, wherein each of the test modules includes  
circuitry configured to route addresses received on the  
dedicated test bus to a corresponding one of the RAM  
blocks, whereby the corresponding one of the RAM blocks  
is accessed in response to the routed addresses.

2. (previously amended) The integrated circuit chip  
of Claim 1, further comprising:

a plurality of pads; and

a switching structure coupled to the plurality of  
pads, wherein the switching structure is configured to  
alternately couple the plurality of pads to the  
dedicated test bus and the system circuitry.

3. (original) The integrated circuit chip of Claim 2,  
further comprising a JTAG controller configured to control  
the switching structure.

4. (original) The integrated circuit chip of Claim 2, wherein the plurality of RAM blocks comprise dual-port and two-port RAM blocks.

5. (original) The integrated circuit chip of Claim 1, wherein the dedicated test bus comprises:

a first set of lines for transmitting address and data signals to the test modules;

a second set of lines for transmitting command signals to the test modules; and

a third set of one or more lines for transmitting a signal for latching the command signals.

6. (original) The integrated circuit chip of Claim 5, wherein the dedicated test bus further comprises a fourth set of lines for transmitting byte-enable signals to the test modules.

7. (original) The integrated circuit chip of Claim 5, wherein the dedicated test bus further comprises a fourth set of lines for transmitting data values from the test modules.

8. (original) The integrated circuit chip of Claim 1, wherein each of the test modules comprises a register for storing a unique address.

9. (original) The integrated circuit chip of Claim 1, wherein each of the RAM blocks includes a multiplexer structure for alternately routing input signals from a corresponding test module or the system circuitry, the

multiplexer structure being controlled by a signal from the corresponding test module.

10. (original) The integrated circuit chip of Claim 1, wherein each of the RAM blocks has a capacity of 32 Kb or less.

11. (presently amended) A method of operating RAM blocks having a capacity less of 32 Kb or less embedded in system circuitry on an integrated circuit chip, the method comprising the steps of:

accessing the RAM blocks through the system circuitry during normal operation of the chip; and

accessing the RAM blocks through a dedicated test bus during a test mode to test the functionality of the RAM blocks prior to normal operation of the chip, wherein the RAM blocks are accessed in response to addresses broadcast on the dedicated test bus.

12. (original) The method of Claim 11, further comprising the steps of accessing the RAM blocks through dedicated test modules coupled to the test bus during the test mode.

13. (original) The method of Claim 12, further comprising the step of storing a unique address in each of the test modules.

14. (original) The method of Claim 11, wherein the chip comprises a plurality of pads, the method further comprising the steps of:

coupling the pads to the system circuitry during normal operation of the chip; and  
coupling the pads to the test bus during the test mode.

15. (original) The method of Claim 14, further comprising the step of controlling the coupling of the pads using a JTAG controller.

16. (original) The method of Claim 11, further comprising the steps of:

writing test data values to the RAM blocks by broadcasting the test data values to all of the RAM blocks on the test bus; and then  
reading test data values from the RAM blocks by individually accessing the RAM blocks on the test bus.

17. (original) The method of Claim 16, further comprising the steps of:

writing test data values to RAM blocks having one write port and to the first write port of RAM blocks having more than one write port; and then  
writing test data values to the second write port of RAM blocks having more than one write port.

18. (presently amended) The method of Claim 12 ~~16~~, further comprising the steps of:

operating the test modules ~~bus~~ in response to a first clock signal provided on the test bus during the test mode; and

operating the RAM blocks in response to a second clock signal provided on the system circuitry during

the test mode, wherein the first clock signal and the second clock signal are independent signals.

19. (previously presented) The method of Claim 18, further comprising adjusting edges of the first clock signal relative to edges of the second clock signal.

20. (canceled)

21. (presently amended) The integrated circuit chip of Claim 1 ~~20~~, wherein the dedicated test bus comprises a clock line for routing a clock signal to each of the test modules.

22. (presently amended) The integrated circuit chip of Claim 1 ~~20~~, wherein each of the test modules further comprises a comparator coupled to receive a unique identification address and the addresses received on the dedicated test bus, wherein the comparator enables a read operation from the corresponding one of the RAM blocks if the unique identification address matches an address received on the dedicated test bus.